

POLYFLOR COLONIA PU

- Colonia - collection of residential vinyl floor products
- Wood effect floorcovering designs
- Coordinating inlay strips to blend, shape or accentuate design ideas

SPECIFICATION



2.0mm



0.2mm



36 @ 101 x 914mm = 3.34m²
 24 @ 152 x 914mm = 3.34m²
 18 @ 152 x 1219mm = 3.34m²
 15 @ 184 x 1219mm = 3.37m²



3680g/m²

LUXURY VINYL
TILES

COLONIA™
FLOORING COLLECTION

WOOD 



GENERAL PERFORMANCE

EN 649
EN ISO 10582



REACTION TO FIRE

EN ISO 13501-1 Class Bfl-S1



SLIP RESISTANCE

EN 13983 Class DS
DIN 51130 R10

For safety flooring with sustainable wet slip resistance, refer to the Polysafe ranges



ABRASION RESISTANCE

EN 649 Group T
EN ISO 10582 Type 1



INDENTATION - RESIDUAL

EN 433 ≤ 0.1mm



DIMENSIONAL STABILITY

EN 434 ≤ 0.25% max.



THERMAL CONDUCTIVITY

Suitable for underfloor heating Max. 27°C



CASTOR CHAIR (continuous use)

Suitable



LIGHT FASTNESS

ISO 105-B02 Method 3 ≥ 6



VOC EMISSIONS

Indoor Air Comfort GOLD - Eurofins certified product
AgBB - Very low emissions
FloorScore - Certified product



ENVIRONMENTALLY PREFERABLE FLOORING

Polyflor Colonia PU achieves a BRE Global Environmental A Rating (Certificate No: ENP 429). Colonia PU is 100% recyclable and contains 15% recycled material. Recyclable via the Recofloor scheme. Visit www.polyflor.com/environment



APPLICATIONS

Colonia PU is ideal for general domestic use.



For information regarding handling and installation, adhesives, maintenance, applications and chemical resistance, consult Polyflor Customer Technical Services on +44 (0)161 767 1912, or email tech@polyflor.com.


* For clarification regarding slip resistance, consult Polyflor.

VARIATION IN COLOUR AND DESIGN IS A FEATURE OF THIS PRODUCT INTENDED TO ENHANCE THE NATURAL APPEARANCE OF THE FLOOR

PERFORMANCE AND PROPERTIES

A BRE
ENP 429
ENVIRONMENTAL
RATING

Refer to BRE Global ratings on www.greenbooklive.com



POLYFLOR LTD. PO BOX 3 RADCLIFFE NEW ROAD WHITEFIELD MANCHESTER M45 7NR UK
 UK SALES DIRECT: +44 (0)161 767 1122 UK SAMPLE REQUESTS: +44 (0)161 767 2551
 EXPORT SALES DIRECT: +44 (0)161 767 1913 TECHNICAL SUPPORT: +44 (0)161 767 1912
 RECEPTION: +44 (0)161 767 1111 UK FAX: +44 (0)161 767 1128
 EXPORT FAX: +44 (0)161 767 1166 E-MAIL: INFO@POLYFLOR.COM
 WEBSITE: WWW.POLYFLOR.COM

James Hallett
FLOORING



2011

POLYFLOR™
COVERING THE WORLD